




**“RELIABLE
QUALITY
&
COMPETITIVE
PRICE”
IT’S OUR TARGET
AND PROMISE**

GAS APPLANCE

BUILT-IN GAS OVEN



MHB-3601S



OPTION
Safety device
for top burner



MHB-3631D
(Built-in Oven + Table Range)

Model	MHB-3601D/3601S	MHB-3631D/3631S
Power Supply	110~120V, 220V~240V, 50~60Hz	
Fuel	LPG / LNG	
Heat Output	9.4kW	40.3kW
Double Burner		12.6kW × 2
Big Burner		5.7kW × 1
Oven Burner	4.8kW × 1	4.8kW × 1
Grill Burner	4.6kW (2.3kW × 2)	4.6kW (2.3kW × 2)
Dimension	W900 × D560 × H785(mm)	W900 × D700 × H975(mm)
Oven Interior	W600 × D430 × H340(mm)	W600 × D430 × H340(mm)
Net Weight	60kg	100kg

Features

- Digital oven temperature indicator
- Front exhaust system
- Oven thermostat
- Built-in motorized rotisserie
- Brushed stainless top, front, side and back guard, oven door handle
- Gas automatic cut-off safety device
(Only for oven and grill burner while option for top burner)
- Direct ignition by electric igniter
- Oven light (MHO-3601D/3631D)
- Alarm bell timer
- Enamel coated oven pan
- Chrome coated mesh
- Individual control for oven and grill burner
- Height adjustable 4 stainless leg
- Durable nylon control knob
- Stainless oven door with tempered glass see-through Window (MHO-3601D/3631D)

* Table range of MHB-3631D/3631S

- Easy cleaning thanks to drawer type drip pan
- Piezoelectric automatic pilot burner ignition
- Convenient 3 position flame control
- Durable cast-iron heavy grate
- 9,200kcal x 2 of super power top double burner




Model	MHB-3602C
Power Supply	110~120V, 220V~240V, 50~60Hz
Fuel	LPG / LNG
Heat Output	4.8kW
Oven Burner	4.8kW × 1
Dimension	W900 × D600 × H590(mm)
Oven Interior	W600 × D430 × H340(mm)
Net Weight	71kg


Features

- Convection oven(Manual)
- Digital oven temperature indicator
- Front exhaust system
- Oven thermostat
- Alarm bell timer
- Gas automatic cut-off safety device for oven
- Oven light
- Direct automatic ignition by electric igniter
- Chrome coated mesh
- Brushed stainless top, front, side and oven door handle
- Height adjustable 4 rubber Legs
- Durable nylon control knob
- Stainless oven door with tempered glass see-through window


HEAVY DUTY GAS OVEN



TOP VIEW



TOP VIEW



TOP VIEW



Model	MHO-3661MO
Power Supply	110~120V, 220V~240V, 50~60Hz
Fuel	LPG / LNG
Heat Output	42.0kW
Big Burner	5.7kW × 6
Oven Burner	7.6kW(3.8kW × 2)
Grill Burner	4.4kW(2.2kW × 2)
Dimension	W640 × D430 × H350(mm)
Oven Interior	W900 × D600 × H1385(mm)
Net Weight	85kg

Features

- Digital oven temperature indicator
- Oven thermostat
- Built-in motorized rotisserie
- Alarm bell timer
- Gas automatic cut-off safety device for oven and grill burner
- Oven light
- Direct automatic ignition by electric igniter
- Chrome coated mesh
- Brushed stainless front, outside and Rooftop back guard
- Enamel coated oven pan
- Individual control for oven and grill burner
- Cast-iron individual top grate
- Height adjustable 4 stainless Legs
- Durable stainless oven door handle
- Durable nylon control knob
- Separated drip pan for each burner
- Stainless oven door with tempered glass See-through window

Model	MHO-3661MC
Power Supply	110~120V, 220V~240V, 50~60Hz
Fuel	LPG / LNG
Heat Output	38.0kW
Big Burner	5.7kW × 6
Oven Burner	7.6kW(3.8kW × 2)
Dimension	W640 × D430 × H350(mm)
Oven Interior	W900 × D600 × H1385(mm)
Net Weight	90kg

Features


- Convection oven(Manual)
- Digital oven temperature indicator
- Oven thermostat
- Alarm bell timer
- Gas automatic cut-off safety device for oven
- Oven light
- Direct automatic ignition by electric igniter
- Chrome coated mesh
- Brushed stainless front, outside and Rooftop back guard
- Enamel coated oven pan
- Cast-iron individual top grate
- Height adjustable 4 stainless Legs
- Durable stainless oven door handle
- Durable nylon control knob
- Separated drip pan for each burner
- Stainless oven door with tempered glass See-through window

Model	MHO-3662SC
Power Supply	110~120V, 220V~240V, 50~60Hz
Fuel	LPG / LNG
Heat Output	24.5kW
Small Burner	3.2kW × 6
Oven Burner	7.6kW(3.8kW × 2)
Dimension	W640 × D430 × H350(mm)
Oven Interior	W900 × D600 × H975(mm)
Net Weight	80kg

Features

- Convection oven(Manual)
- Digital oven temperature indicator
- Oven thermostat
- Alarm bell timer
- Gas automatic cut-off safety device for oven
- Oven light
- Direct automatic ignition by electric igniter
- Chrome coated mesh
- Brushed stainless front, outside and Back guard
- Enamel coated oven pan
- Cast-iron individual top grate
- Height adjustable 4 stainless Legs
- Durable stainless oven door handle
- Durable nylon control knob
- Separated drip pan for each burner
- Stainless oven door with tempered glass See-through window

HEAVY DUTY GAS OVEN




TOP VIEW



Model	MHO-3651S
Power Supply	110~120V, 220V~240V, 50~60Hz
Fuel	LPG / LNG
Heat Output	33.5kW
Big Burner	6.2kW × 1
Small Burner	3.5kW × 4
Grill Burner	4.8kW(2.4kW × 2)
Oven Burner	8.5kW(4.25kW × 2)
Dimension	W900 × D600 × H965(mm)
Oven Interior	W640 × D430 × H350(mm)
Net Weight	75kg

Features

- Oven thermostat
- Built-in motorized rotisserie
- Brushed stainless top, front, side and back guard
- Alarm bell timer
- Gas automatic cut-off safety device (Only for oven and grill burner while Option for top burner)
- Direct automatic ignition by electric igniter
- Enamel coated oven pan and individual drip pan
- Chrome coated mesh
- Individual control for oven and grill burner
- Height adjustable 4 stainless Legs
- Stainless oven door handle
- Cast-iron individual top grate
- Durable & powerful cast-iron top burner body and head
- Stainless oven door
- Aluminum control knob




TOP VIEW



Model	MHO-3651D
Power Supply	110~120V, 220V~240V, 50~60Hz
Fuel	LPG / LNG
Heat Output	33.5kW
Big Burner	6.2kW × 1
Small Burner	3.5kW × 4
Grill Burner	4.8kW(2.4kW × 2)
Oven Burner	8.5kW(4.25kW × 2)
Dimension	W900 × D600 × H965(mm)
Oven Interior	W640 × D430 × H350(mm)
Net Weight	75kg

Features

- Oven thermostat
- Built-in motorized rotisserie
- Brushed stainless top, front, side and Back guard
- Alarm bell timer
- Gas automatic cut-off safety device (Only for oven and grill burner while option for top burner)
- Direct automatic ignition by electric igniter
- Enamel coated oven pan and individual drip pan
- Oven light
- Stainless oven door with tempered glass see-through window
- Chrome coated mesh
- Individual control for oven and grill burner
- Height adjustable 4 stainless Legs
- Stainless oven door handle
- Cast-iron individual top grate
- Durable & powerful cast-iron top burner body and head
- Durable nylon control knob



TOP VIEW




Model	MHO-3652D
Power Supply	110~120V, 220V~240V, 50~60Hz
Fuel	LPG / LNG
Heat Output	40.0kW
Super Burner	10.6kW × 1
Big Burner	5.7kW × 2
Small Burner	3.2kW × 2
Grill Burner	4.4kW(2.2kW × 2)
Oven Burner	7.6kW(3.8kW × 2)
Dimension	W900 × D600 × H965(mm)
Oven Interior	W640 × D430 × H350(mm)
Net Weight	75kg

Features

- Digital oven temperature indicator
- 9,200kcal of super power top double burner
- Oven thermostat
- Alarm bell timer
- Gas automatic cut-off safety device for oven And grill burner
- Oven light
- Direct automatic ignition by electric igniter
- Chrome coated mesh
- Brushed stainless front, outside and back guard
- Enamel coated oven pan
- Individual control for oven and grill
- Cast-iron individual top grate
- Height adjustable 4 stainless Legs
- Durable stainless oven door handle
- Durable nylon control knob
- Built-in motorized rotisserie
- Separated drip pan for each burner
- Stainless oven door with tempered glass see-through window

HEAVY DUTY GAS OVEN



TOP VIEW


B TYPE

Black/ Brown
painted aluminum
control knobs




S TYPE

Chrome plated
aluminum control
knobs



TOP VIEW



TOP VIEW



Model	MHO-4051S
Power Supply	110~120V, 220V~240V, 50~60Hz
Fuel	LPG / LNG
Heat Output	33.5kW
Big Burner	6.2kW × 1
Small Burner	3.5kW × 4
Grill Burner	4.8kW(2.4kW × 2)
Oven Burner	8.5kW(4.25kW × 2)
Dimension	W1000 × D600 × H965(mm)
Oven Interior	W640 × D430 × H350(mm)
Net Weight	85kg

Features

- Oven thermostat
- Built-in motorized rotisserie
- Brushed stainless top, front, side and back guard
- Alarm bell timer
- Gas automatic cut-off safety device (Only for oven and grill burner while option for top burner)
- Direct automatic ignition by electric igniter
- Enamel coated oven pan and individual drip pan
- Chrome coated mesh
- Individual control for oven and grill burner
- Height adjustable 4 legs
- Stainless oven door handle
- Cast-iron individual top grate
- Durable & powerful cast-iron top burner body and head
- Aluminum control knob

Model	MHO-4051D
Power Supply	110~120V, 220V~240V, 50~60Hz
Fuel	LPG / LNG
Heat Output	33.5kW
Big Burner	6.2kW × 1
Small Burner	3.5kW × 4
Grill Burner	4.8kW(2.4kW × 2)
Oven Burner	8.5kW(4.25kW × 2)
Dimension	W1000 × D600 × H965(mm)
Oven Interior	W640 × D430 × H350(mm)
Net Weight	85kg

Features


- Oven thermostat
- Built-in motorized rotisserie
- Brushed stainless top, front, side and back guard
- Alarm bell timer
- Gas automatic cut-off safety device (Only for oven and grill burner while option for top burner)
- Direct automatic ignition by electric igniter
- Oven light
- Enamel coated oven pan and individual drip pan
- Chrome coated mesh
- Individual control for oven and grill burner
- Height adjustable 4 Legs
- Stainless oven door handle
- Cast-iron individual top grate
- Durable & powerful cast-iron top burner body and head
- Durable nylon control knob
- Stainless oven door with tempered glass see-through window

Model	MHO-4052D
Power Supply	110~120V, 220V~240V, 50~60Hz
Fuel	LPG / LNG
Heat Output	40.0kW
Super Burner	10.6kW × 1
Big Burner	5.7kW × 2
Small Burner	3.2kW × 2
Grill Burner	4.4kW(2.2kW × 2)
Oven Burner	7.6kW(3.8kW × 2)
Dimension	W1000 × D600 × H965(mm)
Oven Interior	W640 × D430 × H350(mm)
Net Weight	90kg

Features

- Digital oven temperature indicator
- 9,200Kcal of super power top double burner
- Oven thermostat
- Alarm bell timer
- Gas automatic cut-off safety device for oven and grill burner
- Oven light
- Direct automatic ignition by electric igniter
- Chrome coated mesh
- Brushed stainless front, outside and back guard
- Enamel coated oven pan
- Individual control for oven and grill
- Cast-iron individual top grate
- Height adjustable 4 stainless Legs
- Durable stainless oven door handle
- Durable nylon control knob
- Built-in motorized rotisserie
- Separated drip pan for each burner
- Stainless oven door with tempered glass see-through window

HEAVY DUTY GAS OVEN



TOP VIEW


S TYPE

9 Chrome plated
aluminum control knobs




G TYPE

6 Chrome & 3 Gold (24k)
plated aluminum
control knobs



TOP VIEW



TOP VIEW



Model	MHO-4461S
Power Supply	110~120V, 220V~240V, 50~60Hz
Fuel	LPG / LNG
Heat Output	42.4kW
Big Burner	6.2kW × 3
Small Burner	3.5kW × 3
Grill Burner	4.8kW(2.4kW × 2)
Oven Burner	8.5kW(4.25kW × 2)
Dimension	W1100×D810×H985(mm)
Oven Interior	W820×D650×H360(mm)
Net Weight	155kg

Features

- Oven thermostat
- 2 Built-in motorized rotisserie
- Mirror stainless top, front, side and backguard
- Alarm bell timer
- Gas automatic cut-off safety device (Only for oven and grill burner while option for top burner)
- Direct automatic ignition by electric igniter
- Stainless oven pan and enamel coated individual drip pan
- Chrome coated mesh
- Individual control for oven and grill burner
- Height adjustable 4 Legs
- Stainless oven door handle
- Cast-iron individual top grate
- Durable & powerful cast-iron top burnerbody and head
- Aluminum control knob

Model	MHO-4461D
Power Supply	110~120V, 220V~240V, 50~60Hz
Fuel	LPG / LNG
Heat Output	42.4kW
Big Burner	6.2kW × 3
Small Burner	3.5kW × 3
Grill Burner	4.8kW(2.4kW × 2)
Oven Burner	8.5kW(4.25kW × 2)
Dimension	W1100×D810×H985(mm)
Oven Interior	W820×D650×H360(mm)
Net Weight	155kg

Features


- Oven thermostat
- 2 Built-in motorized rotisserie
- Mirror stainless top, front, side and backguard
- Alarm bell timer
- Gas automatic cut-off safety device (only for oven and grill burner while option for top burner)
- Direct automatic ignition by electric igniter
- Oven light
- Stainless oven pan and enamel coated individual drip pan
- Chrome coated mesh
- Individual control for oven and grill burner
- Height adjustable 4 Legs
- Stainless oven door handle
- Cast-iron individual top grate
- Durable & powerful cast-iron top burner body and head
- Durable nylon control knob
- Stainless oven door with tempered glass see-through window

Model	MHO-4462D
Power Supply	110~120V, 220V~240V, 50~60Hz
Fuel	LPG / LNG
Heat Output	58.0kW
Super burner	10.6kW × 2
Big Burner	5.7kW × 2
Small Burner	3.2kW × 2
Grill Burner	4.4kW(2.2kW × 2)
Oven Burner	7.6kW(3.8kW × 2)
Dimension	W1100×D810×H985(mm)
Oven Interior	W820×D650×H360(mm)
Net Weight	175kg


Features

- Digital oven temperature indicator
- 2 Built-in motorized rotisserie
- 9,200kcal x 2 of super power top doubleburner
- Oven thermostat
- Alarm bell timer
- Gas automatic cut-off safety device for oven and grill burner
- Oven light
- Direct automatic ignition by electric igniter
- Chrome coated mesh
- Brushed stainless front, outside and back guard
- Stainless oven pan and enamel coated individual drip pan
- Individual control for oven and grill
- Cast-iron heavy individual top grate
- Height adjustable 4 stainless Legs
- Durable stainless oven door handle
- Durable nylon control knob
- Durable & powerful cast-iron top burner body and head
- Separated drip pan for each burner
- Stainless oven door with tempered glass see-through window


HEAVY DUTY GAS OVEN



TOP VIEW



TOP VIEW



TOP VIEW



Model	MHO-4461CN
Power Supply	110~120V, 220V~240V, 50~60Hz
Fuel	LPG / LNG
Heat Output	50.5kW
Big Burner	6.2kW × 6
Grill Burner	4.8kW(2.4kW × 2)
Oven Burner	8.5kW(4.25kW × 2)
Dimension	W1100×D810×H985(mm) : MHO-4461CN W1100×D810×H1390(mm) : MHO-4461CR
Oven Interior	W820×D650×H360(mm)
Net Weight	175kg

Features

- Oven thermostat
- 2 Built-in motorized rotisserie
- Brushed stainless top, front, side and back guard
- Alarm bell timer
- Gas automatic cut-off safety device (Only for oven and grill burner while option for top burner)
- Direct automatic ignition by electric igniter
- Stainless oven pan and enamel coated individual drip pan
- Chrome coated mesh
- Individual control for oven and grill burner
- Height adjustable 4 Legs
- Stainless oven door handle
- Heavy cast-iron individual overall top grate
- Durable & powerful cast-iron top burner body and head
- Aluminum control knob

Model	MHO-4461CR
Power Supply	110~120V, 220V~240V, 50~60Hz
Fuel	LPG / LNG
Heat Output	50.5kW
Big Burner	6.2kW × 6
Grill Burner	4.8kW(2.4kW × 2)
Oven Burner	8.5kW(4.25kW × 2)
Dimension	W1100×D810×H985(mm) : MHO-4461CN W1100×D810×H1390(mm) : MHO-4461CR
Oven Interior	W820×D650×H360(mm)
Net Weight	175kg

Features


- Oven thermostat
- 2 Built-in motorized rotisserie
- Brushed stainless top, front, side and back guard
- Alarm bell timer
- Gas automatic cut-off safety device (Only for oven and grill burner while option for top burner)
- Direct automatic ignition by electric igniter
- Stainless oven pan and enamel coated individual drip pan
- Chrome coated mesh
- Individual control for oven and grill burner
- Height adjustable 4 legs
- Stainless oven door handle
- Heavy cast-iron individual overall top grate
- Durable & powerful cast-iron top burner body and head
- Aluminum control knob
- Large back guard with roof

Model	MHO-4461DCN
Power Supply	110~120V, 220V~240V, 50~60Hz
Fuel	LPG / LNG
Heat Output	50.5kW
Big Burner	6.2kW × 6
Grill Burner	4.8kW(2.4kW × 2)
Oven Burner	8.5kW(4.25kW × 2)
Dimension	W1100×D820×H985(mm)
Oven Interior	W820×D650×H360(mm)
Net Weight	175kg


Features

- Oven thermostat
- 2 Built-in motorized rotisserie
- Brushed stainless top, front, side and back guard
- Alarm bell timer
- Gas automatic cut-off safety device (Only for oven and grill burner while option for top burner)
- Direct automatic ignition by electric igniter
- Oven light
- Stainless oven pan and enamel coated individual drip pan
- Chrome coated mesh
- Individual control for oven and grill burner
- Height adjustable 4 Legs
- Stainless oven door handle
- Heavy cast-iron individual overall top grate
- Durable & powerful cast-iron top burner body and head
- Durable nylon control knob
- Stainless oven door with tempered glass see-through window


HEAVY DUTY GAS OVEN



TOP VIEW



TOP VIEW



TOP VIEW



Model	MHO-4851S
Power Supply	110~120V, 220V~240V, 50~60Hz
Fuel	LPG / LNG
Heat Output	58.0kW
Super Burner	10.8kW × 3
Big Burner	5.7kW × 2
Grill Burner	5.8kW(1.93kW × 3)
Oven Burner	8.4kW(4.2kW × 2)
Dimension	W1200 × D750 × H975(mm)
Oven Interior	W1020 × D600 × H360(mm)
Net Weight	220kg

Features

- Digital oven temperature indicator
- World largest & big capacity built-in rotisserie (Max load : 30kg)
- 9,200kcal x 3 of super power top double burner
- Oven thermostat
- Alarm bell timer
- Gas automatic cut-off safety device for oven and grill burner
- Direct automatic ignition by electric igniter
- Chrome coated mesh
- Brushed stainless front, outside and back guard
- Enamel coated big oven pan
- Individual control for oven and grill
- Cast-iron super heavy individual top grate
- Height adjustable 4 stainless Legs
- Durable stainless oven door handle
- Durable nylon control knob
- Built-in motorized rotisserie
- Separated drip pan for each burner

Model	MHO-4851D
Power Supply	110~120V, 220V~240V, 50~60Hz
Fuel	LPG / LNG
Heat Output	58.0kW
Super Burner	10.8kW × 3
Big Burner	5.7kW × 2
Grill Burner	5.8kW(1.93kW × 3)
Oven Burner	8.4kW(4.2kW × 2)
Dimension	W1200 × D750 × H975(mm)
Oven Interior	W1020 × D600 × H360 (mm)
Net Weight	220kg

Features

- Digital oven temperature indicator
- World largest & big capacity built-in rotisserie (Max load : 30kg)
- 9,200kcal x 3 of super power top double burner
- Oven thermostat
- Alarm bell timer
- Gas automatic cut-off safety device for oven and grill burner
- Oven light
- Direct automatic ignition by electric igniter
- Chrome coated mesh
- Brushed stainless front, outside and back guard
- Enamel coated big oven pan
- Individual control for oven and grill
- Cast-iron super heavy individual top grate
- Height adjustable 4 stainless legs
- Durable stainless oven door handle
- Durable nylon control knob
- Built-in motorized rotisserie
- Separated drip pan for each burner
- Stainless oven door with tempered glass see-through window

Model	MHO-4861DC
Power Supply	110~120V, 220V~240V, 50~60Hz
Fuel	LPG / LNG
Heat Output	63.0kW
Super Burner	10.8kW × 3
Big Burner	5.7kW × 3
Grill Burner	5.8kW(1.93kW × 3)
Oven Burner	8.4kW(4.2kW × 2)
Dimension	W1200 × D800 × H975(mm)
Oven Interior	W1020 × D600 × H360 (mm)
Net Weight	230kg

Features

- Convection oven(manual)
- Digital oven temperature indicator
- World largest & big capacity built-in rotisserie (Max load : 30kg)
- 9,200kcal x 3 of super power top double burner
- Oven thermostat
- Alarm bell timer
- Gas automatic cut-off safety device for oven and grill burner
- Oven light
- Direct automatic ignition by electric igniter
- Chrome coated mesh
- Brushed stainless front, outside and back guard
- Enamel coated big oven pan
- Individual control for oven and grill
- Cast-iron super heavy individual overall top grate
- Height adjustable 4 stainless legs
- Durable stainless oven door handle
- Durable nylon control knob
- Built-in motorized rotisserie
- Separated drip pan for each burner
- Stainless oven door with tempered glass see-through window

PORTABLE GAS MULTI WIDE GRILL/STOVE




Model	MHW-2402G
Fuel	Butane Cartridge / 220g
Heat Output	2.65kW
Dimension	W640×D360×H140(mm)
Net Weight	5.3kg

Features

- Piezoelectric automatic ignition
- Super wide grill plate
- One touch filter for oil drain
- Corner oil drain hole
- Multi grate for table top cooker
- Strong flame against plate
- Teflon coated aluminum plate
- Antiskid rubber legs
- Foldable long leg for outdoor use

GAS TABLE COOKER



TOP VIEW



Model	MHR-2422
Fuel	LPG / LNG
Heat Output	12.0kW(6.0kW×2)
Dimension	W596×D525×H165(mm)
Hose Connection	Ø9.5(mm)
Net Weight	16kg

Features

- Piezoelectric automatic ignition
- Convenient 3 position flame control
- Durable stainless body
- High calorific 2 burner
- Stable castiron grate
- Durable nylon control knob
- Enamel coated drip pan
- Durable castiron burner body & head
- Antiskid rubber legs
- Compact design

GAS CABINET STOVE



MHC-2441D




MHC-2441S

Model	MHC-2441D/2441S
Fuel	LPG / LNG
Heat output	30kW(7.5kW×4)
Dimension	W600×D850×H885 / With Backguard : 1020(mm)
Hose Connection	PT 3/4"(20A)
Net Weight	75kg


Features

- Piezoelectric automatic pilot burner ignition
- Convenient 3 position flame control
- Brushed stainless body
- Height adjustable 4 legs
- Easy cleaning thanks to drawer type drip pan
- High calorific 4 burner
- Durable cast-iron overall heavy grate
- Durable & powerful cast-iron top burner body and head
- Back guard
- Stainless cabinet(with door : MHC-2441D)
- Durable nylon control knob


GAS STOCK POT RANGE




TOP VIEW



TOP VIEW



TOP VIEW



TOP VIEW



Model	MHS-2441G	MHS-3661G
Fuel	LPG / LNG	
Heat Output	30kW (7.5kW × 4)	45kW(7.5kW × 6)
Dimension	W600 × D780 × H830 / With Backguard : 920(mm)	W900 × D780 × H830 / With Backguard : 920(mm)
Hose Connection	PT 3/4"(2CA)	
Net Weight	55kg	65kg

Features

- Piezoelectric automatic pilot burner ignition
- Convection 3 position flame control
- Brushed stainless body
- Height adjustable 4 legs
- Easy cleaning thanks to drawer type drip pan
- High calorific 4 burner(2441G) & 6 burner (3661G)
- Durable cast-iron overall heavy grate
- Durable & powerful cast-iron top burner body and head
- Back guard
- Stainless shelf
- Durable nylon control knob
- Durable square stainless pipe leg

Model	MHS-3627G	MHS-3637G
Fuel	LPG / LNG	
Heat Output	25.0kW	31.0kW
Dimension	W900 × D700 × H850/With Backguard : 975(mm)	
Hose Connection	PT 1/2"(15A)	
Net Weight	65kg	70kg

Features

- Piezoelectric automatic pilot burner ignition
- Convenient 3 position flame control
- Brushed stainless body
- Height adjustable leg
- Easy cleaning thanks to drawer type drip pan
- High calorific burner & double burner
- Durable cast-iron heavy grate
- Durable & powerful cast-iron top burner body and head
- Back guard
- Stainless shelf
- Durable nylon control knob
- Durable square stainless pipe leg

Model	MHS-4837G	MHS-4847G
Fuel	LPG / LNG	
Heat Output	39.0kW	42.0kW
Dimension	W1500 × D700 × H850/With Backguard : 975(mm)	
Hose Connection	PT 3/4"(20A)	
Net Weight	75kg	80kg

Features

- Piezoelectric automatic pilot burner ignition
- Convenient 3 position flame control
- Brushed stainless body
- Height adjustable leg
- Easy cleaning thanks to drawer type drip pan
- High calorific burner & double burner
- Durable cast-iron heavy grate
- Durable & powerful cast-iron top burner body and head
- Back guard
- Stainless shelf
- Durable nylon control knob
- Durable square stainless pipe leg

GAS STOCK POT RANGE



Model	MHS-6037G	MHS-6057G
Fuel	LPG / LNG	
Heat Output	39.0kW	50.0kW
Dimension	W1500 × D700 × H850/With Backguard : 975(mm)	
Hose Connection	PT 3/4" (20A)	
Net Weight	75kg	85kg

Features

- Piezoelectric automatic pilot burner ignition
- Convenient 3 position flame control
- Brushed stainless body
- Height adjustable 4 legs
- Easy cleaning thanks to drawer type drip pan
- High calorific burner & double burner
- Durable cast-iron heavy grate
- Durable & powerful cast-iron top burner body and head
- Back guard
- Stainless shelf
- Durable nylon control knob
- Durable square stainless pipe leg

GAS WOK RANGE



Model	MHS-2417G	MHS-4827G	MHS-6027G
Fuel	LPG / LNG		
Heat Output	21.5kW	43.0kW	43.0kW
Dimension	W600 × D700 × H450 / With Backguard:975(mm)	W1200 × D700 × H450 / With Backguard:975(mm)	W1500 × D700 × H450 / With Backguard:975(mm)
Hose Connection	PT 1/2"(15A)	PT 3/4"(20A)	
Net Weight	65kg	85kg	90kg

Features

- Piezoelectric automatic pilot burner ignition
- Convenient 3 position flame control
- Brushed stainless body
- Height adjustable 4 legs
- Easy cleaning thanks to drawer type drip pan
- High calorific triple burner
- Durable cast-iron heavy grate
- Durable & powerful cast-iron top burner body and head
- Back guard
- Durable nylon control knob
- Durable square stainless pipe leg

GAS GRIDDLE



Model	MHG-3621G	MHG-4831G
Fuel	LPG / LNG	
Heat Output	11.4kW	15.2kW
Dimension	W900 × D780 × H830 / With Backguard : 925(mm)	W1200 × D780 × H830 / With Backguard : 925(mm)
Hose Connection	Ø9.5(mm)	
Net Weight	75kg	95kg

Features

- Piezoelectric automatic pilot burner ignition
- Convenient 3 position flame control
- Brushed stainless body
- Height adjustable 4 legs
- Easy cleaning thanks to drawer type drip pan
- Stable temperature control by u-shaped burners
- Ignition flame check windows
- Flame failure safety device(thermocouple)
- Durable & thick steel hot plate (12t)
- Stainless shelf
- Durable nylon control knob
- Durable square stainless pipe leg
- Convenient food scraps outlet

GAS SALAMANDER



Model	MHS-2831G
Fuel	LPG / LNG
Heat Output	7.1kW
Dimension	W825 x D400 x H580(mm)
Hose Connection	Ø9.5(mm)
Net Weight	27kg

Features

- Piezoelectric automatic pilot burner ignition
- Convenient pull & push height control
- Brushed stainless body
- 3 Far infrared ray high efficiency ceramic burner
- Easy flame control (3 step : high-medium-low)
- Independent ignition for each ceramic burner
- Height adjustable 4 legs
- Easy cleaning thanks to overall drip pan
- Durable enamel coated burner casing
- Stainless mesh
- Durable nylon control knob
- Gas governor valve (stable gas supply)
- Floor protect and ignition check reflector

FOR FOOD TRUCK & SPACE LIMITED KITCHEN GAS STOVE



Griddle Pan



For 1 Burner
W300XD330XH75(mm)



For 2 Burner
W600XD330XH75(mm)

Charbroiler



For 1 Burner
W300XD330XH75(mm)

Model	MHR-2421
Fuel	LPG / LNG
Heat Output	15kW(7.5kW x 2)
Dimension	W600 x D500 x H830/ With Backguard : 920(mm)
Hose Connection	Ø9.5(mm)
Net Weight	48kg

Features

- Piezoelectric automatic pilot burner ignition
- Convenient 3 position flame control
- Brushed stainless body
- Height adjustable 4 legs
- Easy cleaning thanks to drawer type drip pan
- High calorific 2 burner
- Durable cast-iron overall heavy grate
- Back guard
- Stainless shelf
- Durable nylon control knob
- Sturdy structure against vibration
- Leg fixer

FOR FOOD TRUCK & SPACE LIMITED KITCHEN GAS SKEWER MACHINE



Model	MHS-3231G
Fuel	LPG / LNG
Heat Output	9.6kW
Dimension	W800 x D500 x H830/ With Backguard : 920(mm)
Hose Connection	Ø9.5(mm)
Net Weight	48kg

Features

- Piezoelectric automatic pilot burner ignition
- Convection 3 position flame control
- Brushed stainless body
- Height adjustable 4 legs
- Easy cleaning thanks to drawer type drip pan
- Back guard
- Stainless shelf
- Durable nylon control knob
- Sturdy structure against vibration
- Leg fixer

GAS FRYER



Metal Fiber Burner

Model	MHF-1824GM	MHF-2436GM
Fuel	LPG / LNG	
Heat output	14.6kW	18.0kW
Oil Tank Capacity	24L	36L
Dimension	W454×D704×H850 With Backguard : 1000(mm)	W550×D700×H850 With Backguard : 1000(mm)
Net weight	52kg	62kg
Electric Consumption	50W	
Power Supply	220~240V, 50~60Hz	
Control Mode	Digital Temperature Control (50℃~190℃)	
Hose Connection	Ø9.5(mm)	

Features

- Excellent temperature restoration thanks to high efficiency metal fiber burner
- Super energy saving mode
- Temperature setting by 1℃ and real time temperature indication
- 8 Channel timer(2 CH : Manual, 6 CH : Program)
- Stable temperature distribution (temperature tolerance : within 1℃)
- Safety device : 1st : PCB High-cut (199℃), 2nd : Bimetal (220℃)
- Durable u shaped heat exchanger

GAS WATER FRYER



Metal Fiber Burner

Model	MHF-2236WG
Fuel	LPG / LNG
Heat output	18kW
Oil Tank Capacity	Water 16.5L/Oil 36.5L
Dimension	W550×D700×H850 With Backguard : 1000(mm)
Net Weight	62kg
Power Supply	220~240V, 50~60Hz
Control Mode	Digital Temperature Control (50℃~190℃)
Hose Connection	Ø9.5(mm)

Features

- Excellent temperature restoration thanks to high efficiency metal fiber burner
- Super energy saving mode
- The life of the frying oil is prolonged as much as 2~3 times
- 8 Channel timer(2CH : Manual, 6CH : program)
- Stable temperature distribution (Temperature tolerance : within 1℃)
- Temperature setting by 1℃ and real time temperature indication
- Safety device : 1st : PCB High-cut (199℃), 2nd : Bimetal (220℃)
- Durable u shaped heat exchanger

AUTOMATIC GAS RICE COOKER

Model	MHR-100	MHR-150
Fuel	LPG/ LNG	
Heat output	22.8kW	34.2kW
Dimension	W750×D700×H914(mm)	W750×D700×H1340(mm)
Net weight	105kg	155kg
Power Supply	220~240V / 50~60Hz	
Power Consumption	45W	59W
Hose Connection	PT 3/4"(20A)	

Features

- Thermal efficiency maximizing energy saving cooking system, save up to 13%.
- Special protective cooking kettle from aluminium to keep discoloration and prevents the scorching of rice.
- Quick cooking system : The combination between central coverage heating system & unique heat insulation plate will keep heat on position, make cooking quicker.
- Our automated gas rice cooker offers the taste of analogue and the convenience of digital technology. All operations are displayed digitally on LCD.

Safety device :

- 1. W-thermistor** : to avoid over-heating and abnormal operation.
 - 2. Two electric valves** : to avoid gas leaking
- Compact body with full solid frame and user-friendly design, thinner & higher than others with control panel on top.
 - Internal battery : possible to cook even the electric current is off.
 - Special function of thermostat and timer sensors to avoid over-cook.
 - Possible to cook various dishes, such as : must potato, curry, porridge, etc.



MHR-100(2Decks)

MHR-150(3Decks)



Special protective aluminium coating kettle



100% Aluminium burner



Rolling rail to put in / out kettle easier & always fit in to position

INDUCTION APPLIANCE

INDUCTION NOODLE COOKER



MHIN-1201E

MHIN-1801E

Model	MHIN-1201E	MHIN-1801E
Power Supply	220V~240V, 50~60Hz	
Electric Consumption	1.3kW	2.6kW(1.3kW × 2)
Dimension	W300 × D440 × H560(mm)	W450 × D440 × H620(mm) Ø210(mm)/Natural pulp cooking vessel
Net Weight	15kg	25kg
Burner Quantity	1ea	2ea
Safety Device	Overheat proof safety device Overcurrent protection safety device Low voltage input prevention safety device Safety device against power failure Cooking vessel reaction sensor	

Features

- One touch setting mode for desired temperature and cooking time.
- Maximum 8 programmable cooking mode
- Cooking alarm after 4~6 min.
- Automatic electric cut-off system when unload cooking vessel

INDUCTION WOK RANGE



Glass Protector

Model	MHIW-2608E	MHIW-2615E
Power Supply	380V, 50~60Hz	
Electric Consumption	8kW	15kW
Dimension	W650 × D650 × H780(mm)	
Net Weight	55kg	
Capacity	60Liter	150Liter
Safety Device	Overheat proof safety device Overcurrent protection safety device Low voltage input prevention safety device Safety device against power failure Pan reaction sensor	

Features

- Convenient to use
- 30% Faster cooking than gas
- 60% Lower energy cost than gas

INDUCTION WOK RANGE



Table top
MHIW-1601ET

Free Standing
MHIW-2401ES

Model	MHIW-1601ET	MHIW-2401ES
Power Supply	220V~240V, 50~60Hz	380V, 50~60Hz
Electric Consumption	5kW	8kW
Dimension	W410 × D600 × H250(mm)	W590 × D650 × H1160(mm)
Net Weight	7kg	55kg
Burner Quantity	1ea	1ea
Safety Device	Overheat proof safety device Overcurrent protection safety device Low voltage input prevention safety device Safety device against power failure Pan reaction sensor	

Features

- 9 Step power output control mode
- Digital timer

INDUCTION RICE COOKER



Model	MHIR-50E
Power Supply	220V~240V, 50~60Hz
Electric Consumption	3.2kW
Dimension	W510×D510×H500(mm)
Net Weight	18kg
Capacity	For 50 Persons
Safety Device	Overheat proof safety device Overcurrent protection safety device Low voltage input prevention safety device Safety device against power failure

Features

- Available even for less than 5 persons
- Control of rice cooking degree is possible thanks to the temperature and time control function
- Not only rice cooking but also steaming and boiling are possible
- Sanitary and excellent thermokeeping triple layered stainless inner kettle



Model	MHIR-100E
Power Supply	220V~240V/380V, 50~60Hz
Electric Consumption	6.4kW(3.2kW×2)
Dimension	W727×D706×H930(mm)
Net Weight	100kg
Capacity	For 100 Persons
Safety Device	Overheat proof safety device Overcurrent protection safety device Low voltage input prevention safety device Safety device against power failure

Features

- Each kettle is for 50 persons
- Control of rice cooking degree is possible thanks to the temperature and time control function
- Sanitary and excellent thermokeeping triple layered stainless inner kettle
- Above 50% energy cost saving, compared with gas



Model	MHIR-150E
Power Supply	220V~240V/380V, 50~60Hz
Electric Consumption	9.6kW(3.2kW×3)
Dimension	W727×D706×H1250(mm)
Net Weight	150kg
Capacity	For 150 Persons
Safety Device	Overheat proof safety device Overcurrent protection safety device Low voltage input prevention safety device Safety device against power failure

Features

- Each kettle is for 50 persons
- Control of rice cooking degree is possible thanks to the temperature and time control function
- Sanitary and excellent thermokeeping triple layered stainless inner kettle
- Above 50% energy cost saving, compared with gas

INDUCTION FRYER



Model	MHIF-2508E
Power Supply	380V, 50~60Hz
Electric Consumption	8kW
Dimension	W620×D860×H1200(mm)
Net Weight	45kg
Capacity	20 Liter
Safety Device	Overheat proof safety device Overcurrent protection safety device Low voltage input prevention safety device Safety device against power failure

Features

- Convenient to use thanks to the temperature control and cooking time reserve function
- Temperature setting by 1℃
- Faster frying by magnetic induction
- Excellent temperature restoration within 2min

INDUCTION SOUP KETTLE/FRYER



Model	MHIS-300E	MHIS-500E
Power Supply	380V, 50~60Hz	
Electric Consumption	20kW	30kW
Dimension	W1670×D1390×H850(mm)	W1750×D1300×H850(mm)
Net Weight	150kg	220kg
Capacity	For 300 persons (150Liter)	For 500 persons(220Liter)
Maximum Gradient	120 Degree	
Safety Device	Overheat proof safety device Overcurrent protection safety device Low voltage input prevention safety device Safety device against power failure	

Features

- Convenient to use thanks to the temperature control and cooking time reserve function with 1~5 steps
- Temperature setting by 1℃
- Sanitary and durable stainless inner kettle
- Easy handle by foldable stainless lid and gradient controller
- Deep-fried food as well as bulk soup

INDUCTION AUTOMATIC STIR-FRIED KETTLE



Model	MHIK-300E	MHIK-500E
Power Supply	380V, 50~60Hz	
Electric Consumption	25kW	30kW
Dimension	W1670×D1390×H850(mm)	W1750×D1300×H850(mm)
Net Weight	153kg	225kg
Capacity	For 300 persons(150 Liter)	For 500 persons(220 Liter)
Maximum Gradient	120 Degree	
Safety Device	Overheat proof safety device Overcurrent protection safety device Low voltage input prevention safety device Safety device against power failure	

Features

- Convenient to use thanks to the temperature control and cooking time reserve function with 1~5 steps
- Temperature setting by 1℃
- Sanitary and double layered stainless inner kettle
- Easy handle by foldable stainless lid and gradient controller

INDUCTION TABLE RANGE



MHIT-1601E

MHIT-1501E

Model	MHIT-1601E	MHIT-1501E
Power Supply	220V~240V, 50~60Hz	
Electric Consumption	3.5kW	5kW
Dimension	W400×D450×H100(mm)	W380×D480×H200(mm)
Net Weight	5kg	7kg
Burner Quantity	1ea	1ea
Safety Device	Overheat proof safety device Overcurrent protection safety device Low voltage input prevention safety device Safety device against power failure Pan reaction sensor	

Features

- 9 Step power output control mode
- Digital timer

2 BURNER INDUCTION TABLE COOKER



Model	MHIT-2702E
Power Supply	220V~240V, 50~60Hz
Electric Consumption	7kW(3.5kW×2) / 10kW(5kW×2)
Dimension	W680×D700×H205(mm)
Net Weight	15kg
Burner Quantity	2ea
Safety Device	Overheat proof safety device Overcurrent protection safety device Low voltage input prevention safety device Safety device against power failure Pan reaction sensor

Features

- 30% Faster cooking than gas
- 60% Lower energy cost than gas

INDUCTION MULTI-RANGE

Features

- Convenient to use by individual temperature control
- 30% Faster cooking than gas
- 60% Lower energy cost than gas



Model	MHIM-3605E	MHIM-5107E	MHIM-6409E
Power Supply	380V, 50~60Hz		
Electric Consumption	2.5kW×2 + 3.5kW×3	2.5kW×7 or 3.5kW×7	2.5kW×9 or 3.5kW×9
Dimension	W915×D730×H331(mm)	W1300×D750×H325(mm)	W1620×D750×H325(mm)
Net Weight	42kg	75kg	85kg
Burner Quantity	5ea	7ea	9ea
Safety Device	Overheat proof safety device Overcurrent protection safety device Low voltage input prevention safety device Safety device against power failure Pan reaction sensor		

ELECTRIC APPLIANCE

ELECTRIC SALAMANDER



Model	MHS-2831EM
Power Supply	220V~240V, 50~60Hz
Electric Consumption	2,850W (950W×3)
Dimension	W700×D400×H540(mm)
Net weight	26kg

Features

- Easy to install
- Instantaneous heating reflection way of high thermal efficiency
- Convenient timer
- Eco-friendly products
- Prebake or multi grill
- Overheat proof safety device
- Convenient button control
- 3 Step flame control (High-Medium-Low)
- Far infrared ray carbon heater
- Floor protect and ignition check reflector
- 2 Position mesh height adjustment

MOBILE ELECTRIC FOOD WARMER

MHW-3051ED (Deluxe type)



MHW-3021ES (Standard type)

Model	MHW-3051ED	MHW-3021ES
Power Supply	220V~240V, 50~60Hz	
Electric Consumption	500W	400W
Dimension	W760×D380×H705(mm)	W730×D380×H700(mm)
Net Weight	35kg	27kg

Features

- Thermostat (MHW-3051ED)
- Wide range temperature control (0~120℃:MHW-3051ED)
- Thermal wire heater
(Top/bottom/left/right/rear:MIHW-3051ED)
- 4 Casters with front 2 stopper
- Brushed stainless body
- Easy and stable temperature control
- Overheat proof safety device (Bi-metal:MIHW-3051ED)
- 3 Microwave safe glass dishes
- Wrap-around sliding tops
- On/Off switch
- Limited temperature control (MHW-3021ES)
- Thermal wire heater (Top/Middle/Bottom:MHW-3021ES)

TABLE TOP ELECTRIC FRYER



Model	MHF-1215ET
Power Supply	220V~240V, 50~60Hz
Electric Consumption	2,500W
Dimension	W300×D460×H240(360)mm
Net Weight	10.5kg
Oil Tank Capacity	5~6L
Control Mode	Digital Temperature Control Mode (Max. Temp. 190℃)
Safety Device	1st:PCB High-Cut(199℃), 2nd:Bimetal(220℃) Electric cut-off safety device against motor rotation

Features

- Easy cleaning by sheath heater rotation
- High thermal efficiency
- Variety kinds of safety device
- Durable contactless ssr heater control mode
- Warmer function
- Easy to move

ELECTRIC FRYER



Model	MHF-1818E	MHF-1821E	MHF-2424E	MHF-2429E
Power Supply	220~240V, 50~60Hz			
Electric Consumption	5,100W	7,000W	7,000W	10,100W
Dimension	W454×D640×H850(955) (mm)		W604×D640×H850(955) (mm)	
Net Weight	35kg		40kg	
Oil Tank Capacity	Approx.18~21.5L		Approx. 24.5~29.5L	
Control Mode	Digital temperature control (50℃~190℃)			
Safety Device	1st:PCB High-Cut(199℃). 2nd:Bimetal(220℃)			

Features

- Easy cleaning by sheath heater rotation
- High thermal efficiency
- 2 Step overheat proof safety device
- Warmer function
- Heater box cover and anti splattering back guard
- No waste gas
- Convenient digital timer
- Durable contactless SSR heater

ELECTRIC WATER FRYER



Model	MHF-1414WE	MHF-2236WE
Power Supply	220~240V, 50~60Hz	
Electric Consumption	3,000W	10,100W
Dimension	W350×D550×H850(920)(mm)	W552×D704×H831(981)(mm)
Net Weight	20kg	53kg
Oil Tank Capacity	Water 8.5L / Oil 14L	Water 17.5L / Oil 36.5L
Control Mode	Digital temperature control (50℃~190℃)	
Safety Device	1st:PCB High-Cut(199℃), 2nd:Bimetal(220℃)	

Features

- The life of the frying oil is prolonged as much as 2~3 times
- No smell issue even in consecutive frying with 2 or more food stuff
- Durable contactless SSR heater
- 2 Step overheat proof safety device
- No waste gas
- Warmer function
- High thermal efficiency
- Easy cleaning by heater box rotation

SMOKELESS ELECTRIC FRYER



Model	MHF-1706SE
Power Supply	220~240V, 50~60Hz
Electric Consumption	2,500W
Dimension	W419×D488×H610(mm)
Net Weight	35kg
Oil Tank Capacity	6.0L
Control Mode	Digital temperature control (50℃~190℃)
Safety Device	Self diagnosis system Triple(thermal sensor/overheat proof/power disconnecting) safety system

Features

- Smellless by eco-friendly dual filtering system (carbon filter + activated carbon)
- Hood filter against oil mist
- Continuous oil mist exhaust by blower fan
- Convenient automatic oil tank lifting system
- Easy to clean by separable heater
- No waste gas
- Convenient digital timer
- Programmable auto cooking menu (30CH)

OIL FILTER MACHINE



Model	MHF-1401E
Power Supply	220V~240V, 50~60Hz
Electric Consumption	250W
Dimension	W345 x D610 x H335(mm)
Filter Paper Size	340 x 470(mm)
Net Weight	24kg
Oil Tank Capacity	Max.43L(Effective:34L)

Features

- Durable motor
- Anti-rust stainless impeller pump
- Heat resistant teflon, silicon and stainless net hose(sanitary & safe)
- Minimum filtering output 1kg/cm²
- Minimum working torque 44kg.f
- Triple layered safe gun hose
- Easy attachable/detachable coupler for gun hose
- 4 Casters with 2 front stopper

* Using temperature : above 150°C

TWO IN ONE DOUGH MIXER

“Automatic dough and coating at a time”



Model	MHM-1222E
Power Supply	220~240V, 50~60Hz
Electric Consumption	40W
Dimension	W300 x D320 x H420 Dough Bowl Ø270(mm)
Net Weight	15kg
Dough Capacity	2kg
Control Mode	Digital

Features

- Labor cost saving
- Programmed kneading time : 10 sec. 30 sec. 40 sec. 60 sec. (selectable)
- Detachable dough bowl
- Automatic dough and coating at a time
- Sanitary stainless bowl
- Maximum coating capacity : 2 chickens

ELECTRIC PROOFER



Model	MHP-2481E
Power Supply	220~240V, 50~60Hz
Electric Consumption	1000W
Dimension	W600xD700XH850(mm)
Net Weight	26kg
Pan. Quantity	8 Pan
Set Temperature	0~50°C
Safety Device	Overheat proof safety device Abnormal current shut-off device Thermistor cut off safety device

ELECTRIC (BAKING) OVEN



Model	MHO-2414ET
Power Supply	220~240V, 50~60Hz
Electric Consumption	3,200W
Dimension	W610×D750×H540(mm)
Net Weight	49kg
Pan Setting	4 (Pan size : W450×D335×H15) Interval in height : 75(mm)
Control Mode	Digital Temperature Control(30℃~230℃)
Safety Device	Overheat proof safety device (300℃) over voltage proof safety device abnormal high temperature proof safety device short circuit proof safety device by thermistor

Features

- Two way rotation convection motor
- Short cooking time by turbo fan
- No need drain piping by water pump
- Easy cleaning for interior by water
- Time, temperature and humidity set (14 Menu)
- Tempered pair glass
- Steam outlet

ELECTRIC (FUSION) OVEN



Model	MHO-2651E
Power Supply	220~240V, 50~60Hz
Electric Consumption	5,000W
Dimension	W660×D710×H630(mm)
Net Weight	70kg
Shelf Setting	5 (Mesh : W380×D380), Shelf Interval in height : 85(mm)
Control Mode	Digital Temperature Control(50℃ ~ 250℃)
Safety Device	Overheat proof safety device (300℃) over voltage proof safety device abnormal high temperature proof safety device short circuit proof safety device by thermistor

Features

- Two way rotation convection motor
- Short cooking time by turbo fan
- No need drain piping by water pump
- Easy cleaning for interior by water
- 5 Timers for 5 shelves
- Durable contactless SSR heater
- Tempered pair glass
- Steam outlet
- Interior drain function



Switch Deck Oven

Rear View

ELECTRIC DECK OVEN

Features

- Convenient temperature control
- Durable and high efficient halogen lamp
- Durable pair glass
- Minimized temperature tolerance ($\pm 2^{\circ}\text{C}$)
- Alarm timer
- Water supply system (solenoid valve)
- Over-heat proof safety device (automatic power shut off at 300℃ and alarm)
- Continuous steam spray (optional)

	Electric Deck Oven	Standard Deck Oven	Switch Deck Oven
Model	MHD-4806E (2pan×3deck) MHD-6309E (3pan×3deck) MHD-6312E (4pan×3deck)	MHD-4806S (2pan×3deck) MHD-6309S (3pan×3deck) MHD-6312S (4pan×3deck)	MHD-4806SW (2pan×3deck) MHD-6309SW (3pan×3deck) MHD-6312SW (4pan×3deck)
Power Supply	220V~240V/380V, 50~60Hz		
Electric Consumption	13.5kW(2pans)/18kW(3pans)/24kW(4pans)		
Dimension	MHD-4806 : W1200×D900×H1800(mm)	MHD-6309 : W1600×D900×H1800(mm)	MHD-6312 : W1600×D1050×H1800(mm)
Control Mode	Digital temperature control		
Baking Pan	400×600(mm)		
Temperature Control Range	Room Temperature ~ 300℃		
Material	- Brushed stainless 1.5t (interior : steel 1.5t, steam : stainless 3.0t) - Tempered glass 5.0t, insulation : super wool		

ELECTRIC CONVECTION OVEN/RACK OVEN



MHC-2910E2



MHC-2905E/2910E



MHR-4214E

Features

- Convenient micro processor jog shuttle
- Durable and high efficient halogen lamp
- Durable pair glass
- Minimized temperature tolerance ($\pm 2^{\circ}\text{C}$)
- Stable heat distribution (two way rotation fan)
- Alarm timer
- Water supply system (solenoid valve)
- Over-heat proof safety device (automatic power shut off at 300°C and then alarm)
- Continuous steam spray
- 10 Programmable memory menu
- Sheath heater

Convection Oven				Electric Rack Oven
Model	MHC-2910E2	MHC-2905E	MHC-2910E	MHR-4214E
Power Supply	220V~240V/380V, 50~60Hz			
Electric Consumption	16kW	8kW/16kW		30kW
Dimension	W730×D1085×H1290(mm)	W730×D1085×H645(mm)/2905E W730×D1085×H1095(mm)/2910E		W1050×D1200×H2100(mm)
Control Mode	Digital Micro Processor			
Baking Pan	400×600(mm)			
Temperature Control Range	Room Temperature ~ 300℃			
Material	Brushed stainless 1.5t (interior : stainless 1.2t) Tempered glass 5.0t, insulation : super wool			Brushed stainless 2.0t (interior : steel 3.0t, CR 3.0t, galvanized plate 2.0t) Tempered glass 5.0t, insulation : super wool

ELECTRIC PROOFER DOUGHNUT FRYER SLICER



Electric Proofer



Doughnut Fryer



Slicer

	Electric Proofer	Electric Doughnut Fryer	Electric Slicer
Model	MHP-2120E MHP-2940E	MHF-2418DE MHF-3218DE	MHS-2307E
Power Supply	220V~240V, 50~60Hz		
Electric Consumption	2kW	3kW / 6kW	0.75kW
Dimension	W520×D900×H1800(mm)/2120E W720×D900×H1800(mm)/2940E	W600×D500×H1060(mm)/2418DE W800×D700×H1080(mm)/3218DE	W570×D630×H610(mm)
Control Mode	Digital control		
Baking Pan	400×600(mm)		
Temperature Control Range	Room Temperature ~ 50°C	120°C ~ 220°C	
Material	- Brushed stainless 1.5t (interior : stainless 0.8t, rack stainless 1.0t) - Tempered glass 5.0t	- Brushed stainless 1.0t (interior : stainless 0.8t)	- Brushed stainless 1.5t (interior : steel 1.5t, treated stainless knife-edge)
Features	- Stable temperature distribution by inner circulation fan - Back door type heater - Automatic water supply (manual is available) - Durable and sanitary stainless 304 interior	- Easy to clean thanks to controller rotation - Over-heat proof safety device (automatic power shut off and then alarm) - Oil tank capacity : 18liter	- Counter top installation - Low noise and vibration - Supporter (optional item)

MEAT THAWING AND DRY AGING REFRIGERATOR



B090CS-3TR



B120CS-3TR



B064BG-1TR



B074BG-1TR



B137BG-2TR

Model	B090CS-3TR	B120CS-3TR	B064BG-1TR	B074BG-1TR	B137BG-2TR
Compressor	1/4+HP	1/4+HP	1/4+HP	1/3 HP	1/3 HP×2
Refrigerant	R-134A	R-134A	R-134A	R-134A	R-134A
Power Supply	220V / 1Ph / 60 Hz	220V / 1Ph / 60 Hz	220V / 1Ph / 60 Hz	220V / 1Ph / 60 Hz	220V / 1Ph / 60 Hz
# Of Shelves	-	-	2	5	10
Capacity	177 Liter	275Liter	225Liter	556Liter	555Liter×2
Power Consumption	199W	253W	262W	362W	724W
Dimension	W906×D700×H840	W1206×D700×H840	W635×D631×H1158	W740×D801×H2065	W1375×D801×H2065

Features

- The temperature distribution in the refrigerator is equally maintained by the indirect cooling method.
- Anion ceramic steel sheet (Mainly made of rare earth ore) is applied for interior.
- Durable high grade stainless steel is applied for exterior.
- Sophisticated and luxurious LCD touch control system is applied.
- Sliding system is applied to the unit for convenient maintenance.
- Wide drawer with various capacity and size is applied according to usage. (Drawer table)
- Apply cool and clean LED lamp that can highlight the atmosphere and product image on store.
- Use durable high-grade stainless steel (SUS304) to shelves.
- Use high-density polyurethane with good thermal insulation.



Ceramic steel sheet with Anion release



Antimicrobial and deodorizing effect



Dry aging



Individual circulating fans



F 557ℓ

B074-1FOOS-E
W740×D803×H1910(mm)



F 1032ℓ

B126-2FFOS-E
W1260×D803×H1910(mm)



F 1251ℓ

B150-2FFOS-E
W1500×D803×H1910(mm)



F 1616ℓ

B190-3FFFS-E
W1900×D803×H1910(mm)



R 557ℓ

B074-2ROOS-E
W740×D803×H1910(mm)



R 1032ℓ

B126-4RROS-E
W1260×D803×H1910(mm)



R 557ℓ

B074S-13ROOS-E
W740×D803×H1910(mm)



R 1032ℓ

B126S-26RROS-E
W1260×D803×H1910(mm)



R 493ℓ F 493ℓ

B126S-24RFOS-E
W1260×D803×H1910(mm)



R 493ℓ F 493ℓ

B126S-23RFOS-E
W1260×D803×H1910(mm)



R 911ℓ F 291ℓ

B150S-22RMOS-E
W1500×D803×H1910(mm)



R 502ℓ

B068B-2ROOS-E
W685×D803×H2025(mm)



R 551ℓ

B074B-2ROOS-E
W740×D803×H2025(mm)



R 787ℓ

B100B-4RROS-E
W1000×D803×H2025(mm)



R 1021ℓ

B126B-4RROS-E
W1260×D803×H2025(mm)



R 1126ℓ

B137B-4RROS-E
W1375×D803×H2025(mm)



R 1600ℓ

B190B-6RRRS-E
W1900×D803×H2025(mm)



R 1126ℓ

B137BH-2RROS(D4)
W1375×D803×H2025(mm)



R 557ℓ

B074H-1ROOS-E
W740×D803×H1910(mm)



R 1032ℓ

B126H-2RROS-E
W1260×D803×H1910(mm)



R 1251ℓ

B150H-2RROS-E
W1500×D803×H1910(mm)



R 1616ℓ

B190H-3RRRS-E
W1900×D803×H1910(mm)



R 502ℓ

B068BH-1ROOS(D2)
W685×D803×H2025(mm)



R 787ℓ

B100BH-2RROS(D2)
W1000×D803×H2025(mm)



R 177ℓ F 177ℓ

B150C-2FROS-E
W1506×D700×H840(mm)



R 177ℓ F 275ℓ

B180C-3FRRS-E
W1806×D700×H840(mm)



R 275ℓ

B120CH-2RROS-E
W1206×D700×H840(mm)



R 370ℓ

B150CH-2RROS-E
W1506×D700×H840(mm)



R 469ℓ

B180CH-2RROS-E
W1806×D700×H840(mm)



R 183ℓ

B070SB-1ROOS-E
W706×D890×H1070(mm)



R 244ℓ

B090SB-2RROS-E
W906×D890×H1070(mm)



R 336ℓ

B120SB-2RROS-E
W1206×D890×H1070(mm)



R 425ℓ

B150SB-2RROS-E
W1506×D890×H1070(mm)



R 518ℓ

B180SB-3RRRS-E
W1806×D890×H1070(mm)



R 232ℓ

B059BBG-1ROOC-E
W596×D688×H990(mm)



R 382ℓ

B124BBG-2RROC-E
W1246×D688×H1045(mm)



R 569ℓ

B146BBG-2RROC-E
W1466×D688×H1045(mm)



R 680ℓ

B172BBG-2RROC-E
W1727×D688×H1045(mm)



R 917ℓ

B226BBG-3RRRC-E
W2268×D688×H1045(mm)